

450MM DIA DEEP INSPECTION CHAMBER [150MM]

Product Data Sheet

| 450mm deep inspection chamber as a single piece system, suitable for adoptable and non-adoptable applications.

PRODUCT CODE - PIC450150

Nominal Diameter | 450mm

Main Inlet and Outlet | 150mm

Side Branches | 4 side branch inlets

- 2 x 110mm x 45°

& 2 x 150mm x 90°

Depths Available




Application

- Maximum installation depth - adoptable 2.0m and non-adoptable 3.0m
- For aboveground access and maintenance inspection of buried pipework up to 3 metres deep
- For pedestrian use - granular backfill
- For vehicle use - concrete backfill

Key Benefits

- Shaft units can be cut to required length
- Lightweight [no heavy lifting]
- Ready to install with no assembly required
- Manufactured in the UK
- Restrictor caps are available for chambers deeper than 1.2m



**Twinwall Shaft Adaptor
to suit SCF45035 cover**

Compliance

- DCG 2020 Chamber Detail - Type D & E
- Sewers for Adoption [SfA7] 7th Edition
- Building Regulations - Part H1



**Manufactured to BS EN 13598-2 &
conforms to building regulations**

For further information, please call 0121 552 8887
sales@polydraincivils.com | www.polydraincivils.com

